

## **POLYESTER ROUND SLINGS**



The Saf/Grip Endless Round Sling is the most versatile. Capable of being used in vertical, choker and basket hitches, wear points can be shifted to extend sling life. Pliable body hugs the load and offers super strength and ease of handling.

Slings features:

- Low Stretch (3%)
- Color Coded Capacities
- Red Striped Whitecore Yarns to Aid Inspection

		поресион					
		Approx. Body	Approx. Body	Rated C			
Color Code	Stock No.	Diameter in Inches	Wt - Pounds/Ft	Vertical	Choker	Basket	Minimum Length
Purple	SR-1	0.60	0.22	2,600	2,100	5,200	3 ft.
Green	SR-2	0.80	0.34	5,300	4,200	10,600	3 ft.
Yellow	SR-3	1.00	0.55	8,400	6,700	16,800	3 ft.
Tan	SR-4	1.20	0.70	10,600	8,500	21,200	3 ft.
Red	SR-5	1.30	0.85	13,200	10,600	26,400	3 ft.
White	SR-6	1.40	1.10	16,800	13,400	33,600	6 ft.
Blue	SR-7	1.75	1.35	21,200	17,000	42,400	6 ft.
Orange	SR-8	2.00	1.50	25,000	20,000	50,000	6 ft.
Orange	SR-9	2.25	1.60	31,000	24,800	62,000	6 ft.
Black	SR-10	2.75	2.30	40,000	32,000	80,000	6 ft.
Black	SR-11	3.25	2.90	53,000	42,400	106,000	7 ft.
Black	SR-12	3.50	3.90	66,000	52,800	132,000	7 ft.
Black	SR-13	4.25	5.00	90,000	72,000	180,000	7 ft.
Black	SR-13S	4.50	5.60	100,000	80,000	200,000	7 ft.
Black	SR-13	4.25	5.00	90,000	72,000	180,000	7 ft.

SAF/GRIP Round Slings are available in Eye & Eye Configuration with Body Protected by Cordura® Tubular Jacket for extra protection.

For 6-Part and 8-Part Braided Round Slings and use in Chemically Active Environment - Consult Factory.



\*\*Warning! Failure to follow proper care, use and inspection criteria may result in personal injury. Do not exceed rated capacities. Horizontal sling angles less than 30° shall not be used.