EPH-Series, Posi Lock[®] Hydraulic Grip Pullers

ENERPAC, 2

V Shown: EPHR-110



- Patented "Safety Cage" jaw retention system
- High force hydraulic system for effortless pulling of large components
- Slim tapered jaws for better gripping in tight spots
- Available in 2 and 3 jaw design
- More efficient pulling, as one man can do the job where normal pullers often require two operators

High-Tech Pulling



Transport and Store

Conveniently store and transport hydraulic pullers and accessories. Order the **EPT-2550** Storage Cart and make your job easier to do!



Long Jaws Used to increase the reach and spread of pullers. They maintain the same pulling capacity as the standard jaws, but


reduce clamping force to 25%.






Application Tip

Because of the unique safety cage design, Posi Lock[®] pullers will grip on surfaces where normal pullers would slip off; e.g. tapered bearings.



Number of Jaws	Max. Spread	Capacity	Model Number*	
	(in)	(ton)		
2	12.00	10	EPH-208	
3	12.00	10	EPH-108	
2	15.00	15	EPH-210	
3	15.00	15	EPH-110	
2	18.00	25	EPH-213	
3	18.00	20	EPH-113	
2	25.00	50	EPH-216	
3	25.00	50	EPH-116	

*Cylinder is not included.



 An EPHR-116, 50-ton hydraulic Posi Lock[®] puller easily removes the main drive gear from this metal forming brake press.

Posi Lock[®] Hydraulic Grip Pullers

EPH Series

▼ SETS SELECTION CHART

Style	Capa- city	Basic Puller	Cylinder	Stroke	Pump Set	Set Model	Weight
	(ton)			(in)		Number	(lbs)
	10	EPH-208	RC-106	6	-	EPHR208	24
	10	EPH-208	RC-106	6	EP-1	EPHS208	60
2	15	EPH-210	RC-1510	10	-	EPHR210	49
Jaw	15	EPH-210	RC-1510	10	EP-1	EPHS210	85
Puller	25	EPH-213	RC-2514	14.25	-	EPHR213	98
	25	EPH-213	RC-2514	14.25	EP-1	EPHS213	118
	50	EPH-216	RC-5013	13.25	-	EPHR216	192
	10	EPH-108	RC-106	6	-	EPHR108	26
	10	EPH-108	RC-106	6	EP-1	EPHS108	62
3	15	EPH-110	RC-1510	10	-	EPHR110	52
Jaw Puller	15	EPH-110	RC-1510	10	EP-1	EPHS110	88
	25	EPH-113	RC-2514	14.25	-	EPHR113	106
	25	EPH-113	RC-2514	14.25	EP-1	EPHS113	126
	50	EPH-116	RC-5013	13.25	-	EPHR116	202




Capacity: 10-50 tons

Maximum Reach: 8.0-14.0 inches

Maximum Spread: 0.75-25.0 inches

Maximum Operating Pressure:

10,000 psi



L	A										▼ *Optional Accessory
	Dimensions (in)							Model Number	្រណ៍	-	
Spread Range	Overall Length	Reach (max.)	Jaw Length	Jaw Width	Tip Clearance	Tip Depth		Number		0	\bigcirc
A	В	С	D	F	G	Н	(lbs)		Ram Point Sets	Lift Plates	*Long Jaws
.75-12.0	19.61	8.00	9.34	.88	.29	.27	14	EPH-208	EPH-155	EPH-11052	EP-11054
.75-12.0	19.61	8.00	9.34	.88	.29	.27	16	EPH-108	EPH-155	EPH-11052	EP-11054
1.0-15.0	26.19	10.00	10.64	1.00	.441	.36	22	EPH-210	EPH-155	EPH-11052	EPH-11054L
1.0-15.0	26.19	10.00	10.64	1.00	.441	.36	25	EPH-110	EPH-155	EPH-11052	EPH-11054L
2.5-18.0	33.31	12.00	13.72	1.25	.508	.38	47	EPH-213	EPH-257	EPH-11352	EP-11354L
2.5-18.0	33.31	12.00	13.72	1.25	.508	.38	55	EPH-113	EPH-257	EPH-11352	EP-11354L
3.0-25.0	36.19	14.00	16.29	1.44	.598	.46	90	EPH-216	EPH-508	EPH-11652	EPH-21654L
3.0-25.0	36.19	14.00	16.29	1.44	.598	.46	100	EPH-116	EPH-508	EPH-11652	EPH-11654L

For full details on puller accessories see page 156.

A T

в

D

* Long Jaws are available as optional accessories.

Posi Lock[®] Puller Accessories

ENERPAC. 2 POWERFUL SOLUTIONS. GLOBAL FORCE.

▼ RAM POINT SETS SELECTION CHART

Fits Model Number	EPH-208 EPH-108 EPH-210 EPH-110	EPH-213 EPH-113	EPH-216 EPH-116	
			<u>A</u>	
Set Number	EPH-155	EPH-257	EPH-508	
Set Includes	Dia. x Length (in)	Dia. x Length (in)	Dia. x Length (in)	
	1 x 1	1.5 x 2.25	2 x 3	
Flat Ram Point	1 x 3	2 x 2.25	2.75 x 3	
	_	2 x 4	2.75 x 5	
	1 x 1.5	1.5 x 2.5	2 x 3.75	
Tapered Ram Point	1 x 3.5	2 x 2.5	2 x 3.75	
	_	2 x 4.5	2.75 x 5.5	
Ram Point Adaptor	_	-	2.75 x 2.25	



Always wear Safety Goggles and Gloves while using pullers.

▼ LIFT PLATE SELECTION CHART

Fits Puller Set Model Number	Model Number *	Thickness	Diameter	
		(in)	(in)	
EPH-208	EPH-11052	.25	6	
EPH-108	EPH-11052	.25	6	
EPH-210	EPH-11052	.25	6	
EPH-110	EPH-11052	.25	6	
EPH-213	EPH-11352	.38	8	
EPH-113	EPH-11352	.38	8	12 al
EPH-216	EPH-11652	.38	10	0.000
EPH-116	EPH-11652	.38	10	

* Mounting screws included. Lifting plates are standard included with EPH-Series Pullers.



▲ EPHR-116 used to remove electric motor pulleys. Puller is positioned using the Lift Plate.

▼ LONG JAW SELECTION CHART

Model Number	Fits Puller Set Model Number	No. of Jaws Required	Spread Dimensions	Reach	Weight (each)	<u> </u>	
			(in)	(in)	(lbs)		
EP-11054	EPH-208	2	2.25 - 15.0	9.7	2.5		◄
	EPH-108	3	2.25 - 15.0	9.7	2.5		
EPH-11054L	EPH-210	2	1.5 - 22.0	15.8	5.5		
	EPH-110	3	1.5 - 22.0	15.0	5.5		
EP-11354L	EPH-213	2	1.5 - 30.0	20.0	10.5	-	
	EPH-113	3	1.5 - 30.0	20.0	10.5		

EPH-11054L Long Jaws are used for added reach and spread. They have the same load capacity as standard jaws with 25% of the clamping force.

www.enerpac.com