



Machining & Welding  
www.MachiningAndWelding.com  
Sales@MachiningAndWelding.com

## Spreader Beams Fixed Spread Beams

### Fixed Spread Beams

- Manufactured to exceed all ASME B30.20 and OSHA regulations.
- Painted safety yellow for increased visibility.
- ALL** Spreader Beams shipped with proof load certification paperwork.
- Durable construction ideally suited to jobsite or warehouse use.
- Standard with swivel latch hooks.
- Made in U.S.A.
- Top rigging available - call for details.
- Custom lettering available - call for details.
- Custom designs available - call for engineering.
- ALL** lifting equipment individually proof loaded per OSHA requirements.
- Minimum horizontal top rigging angle of 45°.
- Ideally suited for adding stability to critical lifts.

Working Load Limit in Pounds*	Model Number Headroom (in) Weight (lbs)	Outside Spread (L) in Feet*							A (in) C (in) E (in)
		4	6	8	10	12	16	20	
4,000	<b>Part Number</b>	<b>13094</b>	<b>13097</b>	<b>13100</b>	<b>13103</b>	<b>13106</b>	<b>13109</b>	<b>13112</b>	1.00
	HR =	7.37	7.37	8.12	8.12	8.12	8.12	8.12	0.50
	LBS =	30	50	90	110	130	172	215	.089
10,000	<b>Part Number</b>	<b>13116</b>	<b>13119</b>	<b>13122</b>	<b>13125</b>	<b>13128</b>	<b>13131</b>	<b>13134</b>	1.31
	HR =	8.23	8.98	8.98	8.98	9.98	9.98	9.98	0.75
	LBS =	36	87	112	140	190	250	306	1.08
20,000	<b>Part Number</b>	<b>13138</b>	<b>13141</b>	<b>13144</b>	<b>13147</b>	<b>13150</b>	<b>13153</b>	<b>13156</b>	1.66
	HR =	9.25	11.00	11.00	11.00	11.00	12.00	12.00	1.00
	LBS =	55	115	140	170	195	380	470	1.31



\* Minimum horizontal top rigging angle is 45° on all fixed and adjustable spreaders. M&W recommends a minimum horizontal top rigging angle of 60°.

RFID TRACKING



CHIP EQUIPPED

