Grade 80 Alloy Chain

SPECTRUM 8® ALLOY CHAIN



- Alloy Steel.
- Heat Treated.
- Finish – Black rust preventative coating.
- Permanently embossed with manufacturer's marking and 8 (Grade).
- Proof Tested at 2 times the Working Load Limit with certification.
- Standard container – fiber drum.

Grade 80 Alloy Chain recommended for overhead lifting applications.

Chain Size (in.)	Spec. 8 Drum Stock No.	Feet Per Drum	Material Size (in.)	Working Load Limit (lbs.)*	Maximum Inside Length (in.)	Maximum Inside Width (in.)	Maximum Length 100 Links (in.)	Weight Per 100 Feet (lbs.)
9/32 (1/4)	273527	500	.276	3500	.87	.42	90	72
5/16	273536	500	.343	4500	1.01	.49	100	114
3/8	273545	500	.394	7100	1.23	.58	125	148
1/2	273554	300	.512	12000	1.57	.77	164	243
5/8	273563	200	.630	18100	1.93	.90	202	351
3/4	273572	100	.787	28300	2.42	1.14	252	584
7/8	273581	100	.866	34200	2.66	1.26	277	705
1	273590	75	1.024	47700	3.28	1.54	328	1041
1-1/4	273599	66	1.260	72300	4.03	1.89	403	1478

* Proof loaded at 2 times Working Load Limit. Ultimate Load is 4 times the Working Load Limit.

Crosby provides two methods of attaching Spectrum 8® chain to Crosby fittings.



A-1337
LOK-A-LOY®
Connecting Link
Refer to Page 221



S-1325
Grade 100
Coupler Lilnk
Refer to Page 231

Copyright © 2013 The Crosby Group LLC
All Rights Reserved