Machining & Welding
www.MachiningAndWelding.com

Sales@MachiningAndWelding.com


Twin Hoist Lifting Beams


- Manufactured to exceed all ASME B30.20 and OSHA regulations.
- Painted safety yellow for increased visibility.
- **ALL** Lifting Beams proof loaded and shipped with certification paperwork.
- Durable construction ideally suited to jobsite or warehouse use.
- Made in U.S.A.
- Custom lettering available - call for details.
- Custom designs available - call for engineering.
- **ALL** lifting equipment individually proof loaded per OSHA requirements.
- All dimensions in inches unless otherwise noted.

RFID TRACKING

CHIP EQUIPPED

- Quick and easy lifting of loads with two hoists. Lifting must be done within 5° of vertical.
- Ideally suited to low headroom applications.
- Alloy swivel hook bottom standard connection.
- Load-bearing swivel hook, eye hook, and custom connections available - call for ordering assistance.





Working Load Limit in Pounds*	Part number Headroom Weight	Spread in Feet - L								A	B	C	D	E
		6	8	10	12	14	16	18	20					
4,000	**Part number** HR= Weight	**16427** 15.10 140	**16428** 16.10 191	**16429** 16.10 260	**16430** 17.10 320	**16431** 18.10 560	**16432** 18.10 640	**16433** 19.10 765	**16434** 20.10 1,055	3.0	5.0	0.88	0.63	0.96
6,000	**Part number** HR= Weight	**16435** 16.50 150	**16436** 17.50 225	**16437** 18.50 265	**16438** 18.50 485	**16439** 19.50 600	**16440** 19.50 690	**16441** 20.50 960	**16442** 20.50 1,260	3.0	5.0	1.00	0.63	1.08
10,000	**Part number** HR= Weight	**16443** 22.31 300	**16444** 22.31 380	**16445** 22.31 470	**16446** 23.31 670	**16447** 23.31 920	**16448** 23.31 1,040	**16449** 25.31 1,005	**16450** 25.31 1,305	3.0	5.0	1.00	0.75	1.56
15,000	**Part number** HR= Weight	**16451** 25.75 310	**16452** 26.75 395	**16453** 26.75 580	**16454** 26.75 810	**16455** 28.75 950	**16456** 31.75 1,215	**16457** 31.75 1,575	**16458** 31.75 1,740	4.0	7.0	1.00	0.75	2.17
20,000	**Part number** HR= Weight	**16459** 27.53 370	**16460** 27.53 585	**16461** 29.53 725	**16462** 32.53 975	**16463** 32.53 1,565	**16464** 32.53 1,770			4.0	7.0	1.25	1.00	2.28

* Call for specifications on larger sizes and capacities