McKissick® Snatch Blocks






416 WITH HOOK



All Alloy Snatch Blocks

- Entire block made from heat treated alloy steel. Use of heat treated alloy gives block only 60% of the weight of blocks of comparable capacities.
- Available with a bronze bushed or roller bearing sheaves.
- Easy opening feature of "Champion" blocks retained.
- Hook and shackle assemblies can be interchanged.
- Pressure lube fittings.
- Can be furnished with S-4320 hook latch.
- Blocks furnished with dual rated wireline sheaves.
- Fatigue Rated.



• All sizes are **RFID EQUIPPED**.

417 WITH SHACKLE



416 / 417 / 402 Alloy Snatch Blocks

		Stock No.			Wire	Wa ukin a	Weight Each (lbs.)				
Sheave Diameter (in.)	Bearing Code	416 with Hook	417 with Shackle	402 Tail Board	Rope Size (in.) †	Working Load Limit (t)*	416 with Hook	417 with Shackle	402 Tail Board	Rep. Sheave Stock No.	Rep. Latch Stock No.
6	BB	193427	168972	179238	3/4 - 7/8	12	26	27	15	460824	1096609
6	RB	193472	193757	179283	3/4 - 7/8	12	26	27	15	472679	1096609
8	BB	193490	168990	179318	3/4 - 7/8	12	33	34	21	461173	1096609
8	RB	193542	193819	179363	3/4 - 7/8	12	33	34	21	473286	1096609
10	BB	193613	193882	179434	3/4 - 7/8	12	41	42	29	461814	1096609
10	RB	193677	193935	179498	3/4 - 7/8	12	41	42	29	473785	1096609

* Ultimate Load is 4 times the Working Load Limit.

† May be furnished in other wire rope sizes.

NOTE: When ordering, please specify: size, block number, hook or shackle, bronze bushed or roller bearing, and wire rope size. NOTE: Tail board does not contain the spool that is required with the hook (416) and shackle (417) snatch blocks.

