



ELECTRIC PUMP

PE60 Series
Post Tensioning
56 cu. in./min. Two-Speed



- COMPACT, LIGHT WEIGHT PUMP. EXCELLENT CHOICE FOR RUGGED APPLICATIONS AND LOW VOLTAGE STARTING.**
- Long, trouble free life in the most demanding work environments. For operating single- or double-acting cylinders, or stressing jacks.
 - Powered by 1½ hp, 115 volt, 60/50 Hz single phase motor. Starts under load, even at the reduced voltages at construction sites.
 - Optional fan-driven external oil cooler includes rollover guard.
 - Insulated carrying handle.
 - Integral 4" dia. fluid-filled pressure gauge with steel bezel complies with ASME B40.1 Grade A. With 0 to 10,000 psi pressure range in 100 psi increments.
 - Sealed ¾ gallon (usable) reservoir. Reservoir drain port is standard.
 - Standard oil level sight gauge for accurate oil level monitoring.
 - External spin-on filter removes contaminants from circulating oil to maximize pump, valve and cylinder/tool life.



Pump No.	Max. Pressure Output		dBa at 10,000 (psi)	Amp Draw at 10,000 (psi)	Oil Del. (cu. in./min. @)				A	B	C	D	E	F	G	Prod. Wt. w/Oil (lbs.)
	(psi)	rpm			100 (psi)	700 (psi)	5,000 (psi)	10,000 (psi)	(in.)	(in.)	(in.)	(in.)	(in.)	(in.)	(in.)	
PE604T	10,000	12,000	80/85*	25	704	440	74	56	9 ⁵ / ₁₆	11 ¹ / ₂	18 ¹ / ₄	6	15	4	3/8 NPTF	50
PE604PT	10,000	12,000	80/85*	25	704	440	74	56	9 ⁵ / ₁₆	11 ¹ / ₂	18 ¹ / ₄	6	15	4	3/8 NPTF	51

NOTE: Unloading pressure is 1,000 psi.


For 220/230 volt, 50/60 Hz, single-phase models, add -220 suffix.

Consult factory for PE60 pump models with other control and valve options.



PE604T

10,000 psi



The PE60 used for pre-stressing.



For use with Cyl. Type	Description	Order No.	Valve Type	Valve No.	Valve Function	Control Switch	Motor	Reservoir Usable (cu. in.)
Single-Acting, Spring Seat, Stressing Jack or Double-Acting	1 $\frac{1}{8}$ hp pump with $\frac{3}{4}$ gal. reservoir & valve for double-acting systems.	PE604T	4-Way 3-position	9500	Advance Hold Return	On/Off/Pulse	1 $\frac{1}{8}$ hp, 115 VAC 60/50 Hz, Single Phase	157
Single-Acting or Double-Acting Power Seat, Stressing Jacks Only	PE604T, except has special valve for post tensioning application only.	PE604PT	4-Way 3-position	9628 Model C	Advance Hold Sequenced Return	On/Off/Pulse	1 $\frac{1}{8}$ hp, 115 VAC 60/50 Hz, Single Phase	157
OPTIONAL								
252511: Oil cooler kit for PE604T or PE604PT, 115 VAC. Weight 5 lbs. 252512: Oil cooler kit for PE604T or PE604PT, 220 VAC. Weight 5 lbs.								