



8 x 19 Classification Wire Rope

Strands: 8

Wires Per Strand: 15 to 26

Core: FC & IWRC



IWRC



Fiber Core

Grade: IPS, EIPS

Finish: Bright

Spec: RRW 410D

Diameter Inches	Minimum Breaking Strength in Pounds				Approximate Weight Pounds per Foot	
	IPS IWRC	IPS F.C.	EIPS IWRC	EIPS FC	IWRC	FC
1/2"	20,400	18,460	23,400	20,400	0.47	0.39
9/16"	25,600	23,200	29,400	25,600	0.60	0.50
5/8"	31,400	28,600	36,200	31,400	0.73	0.61
3/4"	45,200	41,000	51,800	45,200	1.06	0.88
7/8"	61,000	55,400	70,000	61,000	1.44	1.20
1"	79,200	72,000	91,000	79,200	1.88	1.57
1 1/8"	99,600	90,600	114,600	99,600	2.39	1.99
1 1/4"	122,600	111,400	141,000	122,600	2.94	24.50
1 3/8"	147,600	134,200	169,800	147,600	3.56	2.97
1 1/2"	174,600	158,800	200,000	174,600	4.24	3.53

* Acceptance strength is not less than 2.5% below the nominal breaking strength as listed.

** For information on sizes not shown in the above table please contact our sales department.

www.allwayinc.com

4 Industrial Drive Bowling Green, MO 63334 Phone: 800-920-3330 Fax: 573-324-5260