


McKissick® Utility Crane Blocks

380 Series Hook Blocks

- Wide range of product available.
 - Capacity: 5 to 300 tons - Larger Models Available.
 - Sheave Sizes: 10" to 30".
 - Wire Line Sizes: 7/16" to 1-3/8".
- Manufactured by an ISO 9001 and API Q1 certified facility.
- All single point shank hooks are genuine Crosby®, forged alloy steel, Quenched and Tempered, and have the patented **QUIC-CHECK®** markings (Duplex hooks are available on all sizes).
- All 380 Blocks are furnished standard with Roller Bearings.
- Reeving Guide Standard – All Models.
- Blocks thru 25 tons use 319N style hooks with S-4320 latches.
- Sheaves lubrication through center pin – separate lube channel to each bearing.
- Sheave fully protected by side plates.
- Dual action hook (swings and rotates).
- Repair parts available through world wide distribution network.
- Design Factor of 4 to 1 (unless otherwise noted).
- All 380 blocks, 16" and larger, are furnished with McKissick® Roll-Forged™ sheaves with flame hardened grooves.
- "Look for the Orange Hook . . . the mark of genuine McKissick® quality".



The patented McKissick Split-Nut® is the standard retention system for standard crane blocks up to 100 tons.

For custom orders contact our Specials Sales Department or reference the special request form on page 445.

OPTIONS AVAILABLE

- Bronze Bushed Sheaves
- Duplex Hooks
- Swivel Tee and Shackle Assemblies
- Sheave Shrouds
- Anti Rotation Hook - Locking Device
- Plate Steel Cheek Weights
- Third party testing with Certification available upon request.

Dead End Chart (Double, Triple, & Quad Sheave Blocks*)

Wire Rope Size (in.)	Dimensions (in.)		Recommended Wedge Socket	
	T Thickness	U Hole Diameter	McKissick® US-422 / US-422T Utility Socket	
			Stock No.	Size
7/16	1.00	1.28	1044309+	US4 7/16
1/2	1.00	1.28	1044318+	US4 1/2
9/16	1.00	1.28	1044336+	US5 9/16
5/8	1.00	1.28	1044345+	US5 5/8
3/4	1.25	1.66	1044363+	US6 3/4
7/8	1.25	1.66	1038580	US7 7/8
1	1.25	1.66	1044417+	US8 1
1-1/8	1.75	2.56	1044426+	US10 1-1/8
1-1/4	1.75	2.56	1044435+	US10 1-1/4

* To find Dead End Dimensions for Single Sheave blocks, refer to table on pages 296.

+ US-422T Terminator Style.