




## 6 x 26 (WS) + IWRC Swaged Wire Rope

**Strands:** 6  
**Wires Per Strand:** 15 to 26  
**Core:** IWRC



**IWRC**

**Grade:** EIPS  
**Finish:** Bright  
**Spec:**

| Diameter in Inches | Minimum Breaking Strength<br>in Pounds | Approximate Weight<br>Pounds per Foot |
|--------------------|----------------------------------------|---------------------------------------|
| 3/8                | 17,700                                 | 0.31                                  |
| 7/16               | 24,500                                 | 0.42                                  |
| 1/2                | 31,600                                 | 0.56                                  |
| 9/16               | 39,600                                 | 0.71                                  |
| 5/8                | 49,000                                 | 0.87                                  |
| 11/16              | 59,200                                 | 1.05                                  |
| 3/4                | 69,800                                 | 1.25                                  |
| 7/8                | 94,600                                 | 1.69                                  |
| 1                  | 120,000                                | 2.22                                  |
| 1 1/8              | 143,000                                | 2.81                                  |
| 1 1/4              | 176,000                                | 3.47                                  |
| 1 3/8              | 210,000                                | 4.19                                  |
| 1 1/2              | 250,000                                | 4.99                                  |

\* Acceptance strength is not less than 2.5% below the nominal breaking strength as listed.

\*\* For information on sizes not shown in the above table please contact our sales department.

[www.allwayinc.com](http://www.allwayinc.com)

4 Industrial Drive Bowling Green, MO 63334 Phone: 800-920-3330 Fax: 573-324-5260